

Q-SUN solar

Onyx Series

Full Black Mono-Crystalline 480~500W

0~+5W POWER TOLERANCE

- High efficiency N - type Double glass black grid solar module
- Stronger properties, PID resistance, reduced hot spot loss
- Better temperature coefficient
- Harsh environmental adaptation
- Full black module, aesthetic appearance
- Bifacial module, more power generation

15 years material warranty **15**

30 years power linear warranty **30**

120

HALF-CUT
CELLS

**182
x182
mm**

SQUARE
CELLS

Comprehensive quality management system
and product certification



IEC61215(2016), IEC61730(2016)
ISO9001:2015: Quality management system
ISO14001:2015: Environmental management system
ISO45001:2018: Occupational health and safety management system

23.1%

MAXIMUM CONVERSION

0~+5W

POWER TOLERANCE


0.4%

0.4% PER YEAR OVER 30 YEARS

Half-Cut Module

LOWER TEMPERATURE COEFFICIENT

Mechanical Diagrams



Length: ±2mm Width: ±2mm Thickness: ±1mm Hole pitch: ±2mm

Packing Standard

Container capacity(40HQ)

Pallet size (mm) : 37pcs/pallet, 24pallets/ctns, 888pcs/ctn

Electrical Parameters At BNPI

Parameter	529	535	540	546	551
Maximum Power (Pmax)	529	535	540	546	551
Open Circuit Voltage (Voc)	43.93	44.20	44.33	44.52	44.71
Short Circuit Current (Isc135)	15.25	15.32	15.38	15.44	15.51
Short Circuit Current (Isc300)	16.99	17.06	17.13	17.20	17.27
Maximum Power Voltage (Vmp)	36.70	36.94	37.18	37.41	37.65
Maximum Power Current (Imp)	14.42	14.48	14.53	14.59	14.64

Electrical Parameters

Module Type	QN-480HT-06		QN-485HT-06		QN-490HT-06		QN-495HT-06		QN-500HT-06	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	480	363	485	367	490	370	495	374	500	378
Open Circuit Voltage (Voc)	43.93	41.73	44.20	41.99	44.33	42.11	44.52	42.29	44.71	42.48
Short Circuit Current (Isc)	13.83	11.07	13.89	11.11	13.95	11.16	14.01	11.21	14.06	11.25
Maximum Power Voltage (Vmp)	36.70	34.68	36.94	34.91	37.18	35.13	37.41	35.36	37.65	35.58
Maximum Power Current (Imp)	13.08	10.46	13.13	10.50	13.18	10.54	13.23	10.58	13.28	10.62
Module Efficiency -ηm (%)	22.2		22.4		22.6		22.9		23.1	


Load Capacity

Max Load Front	5400Pa
Max Load Back	2400Pa
Through Hail Testing	25mm Diameter, Impact Speed 23m/s

Temperature Coefficient (STC Test)


Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Pmax	-0.30%/°C

Curve Figure



Specification

Cell Type	Mono Crystalline
No. of Cells	120 [2x(6x10)] pcs
Dimension	1910x1134x30mm
Weight	26.5kg
Front Glass	2.0mm
Back Glass	2.0mm
Junction Box	IP68
Cable Length	300mm,1200mm(can be customized)



Operation Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC (IEC)
Maximum Series Fuse Rating	25A
Power Tolerance	0~+5W
Nominal Operating Cell Temperature (NOCT)	42±2°C
Safety Class	Class II
Fire Safety Class According	Class C
Refer.Bifacial Factor	80±10%

STC : Irradiance:1000W/m² | Battery temperature: 25°C | Atmospheric=1.5

NOCT: Irradiance:800W/m² | Ambient temperature: 20°C | Atmospheric=1.5 | Wind speed 1m/s

BNPI: Rear Irradiance 135W/m² | Bifaciality coefficient 80%±5%

D5 Greenland Window Building
Nonghua Road
Yuhuatai District, Nanjing, China
www.q-sunsolar.com

