

**5kWh (51.2V/100Ah)**

## Product Features

---



### Class-A LiFePO4 Battery

Cycle Life 6000+  
High Safety and Performance



### Intelligent BMS

50+ Protection Algorithms for Safety and Longer Lifespan  
Number of Parallel: 15



### High Compatibility

Self-adaptive Communication with Mainstream Inverter

Model	QCL-51.2-100	Wall-mounted ESS Battery
Battery Type	LiFePO <sub>4</sub> (LFP) – A Grade Cells	
Nominal Voltage	51.2V	
Nominal Energy	5.12kWh	
Nominal Capacity	100Ah	
Operating Voltage Range	40V-58.4V	
Standard Charging Current	50A	
Maximum Continuous Charging Current	100A	
Cut-Off Charging Voltage	58.4V	
Cut-Off Charging Current	2A	
Standard Discharging Current	100A	
Maximum Continuous Discharging Current	100A	
Maximum Pulse Discharging Current	150A	
Cut-Off Discharging Voltage	40V	
Cut-Off Discharging Current	2A	
Dimensions (L×W×H)	650mm * 370mm * 236.5mm (including bracket)	
Weight	≈50kg	
Communication Port	RS485 / CAN / RS232	
Maximum Parallel Units	15	
Working Temperature (Charge)	0 °C- 55 °C	
Working Temperature (Discharge)	-20 °C - 60 °C	
Ingress Protection	IP20	
Cooling Method	Natural Cooling	
Humidity Range	10%-95%	
Altitude	≤2000m	
Shell Material	Metal	
Current Limiting Function	10A	
Precharge Function	Enabled	
Display	LED	
Cell Configuration	1P16S	
Design Life	10 Years	
Cycle Life	>6000 cycles (@25 °C, 0.5 C, 80 % DOD)	
Certification Level	IEC62619 \ UN38.3 \ MSDS \ DGM	